

'Choices' PremiLine Sliding Patio Door

Sliding Patio Door

Smooth sliding operation with stylish looks



Standard Specification (includes glazing):

- ✓ 70mm profile depth with internally glazed sculptured beads
- ✓ Black gaskets with woolpile weatherseals
- ✓ White (chrome and gold effect upgrades) handles
- ✓ Six point six hook locking
- ✓ Fully welded and reinforced
- ✓ Stainless steel adjustable rollers on a stainless steel track
- ✓ Slides on outer track as standard inner track on request
- ✓ 28mm toughened sealed units with Low E Plus Argon gas and warm edge spacer
- ✓ PVCU profiles using 'greenline' 100% lead free stabilizer
- ✓ 20mm low aluminium threshold available (lower weather rating)
- ✓ Mechanically jointed outer frame available
- ✓ Sliding pane external as standard can be specified to be internal
- ✓ 1.4W/m²K 'U' value with Low-E Plus glass
- ✓ 32mm triple glazing option
- ✓ Ultion One Cylinder



Door Sizes - Maximum

2 Pane 3000mm width x 2300mm height

3 Pane 4200mm width x 2300mm height

4 Pane 5800mm width x 2300mm height

NB: The height of the sash must not be more than 2.5 times larger than the width e.g. Frame height 2090mm means minimum frame width of 1600mm

Colour Options







ULTION 1 PLUS

Both sides only white base



Available both sides or on smooth white



Anthracite Cream Grey

Available on smooth white only



Available on smooth white only extra lead time



6 'Choices' Premiline



PremiLine PRO PAS 24 Upgrade

'Lifetime Homes' and 'Document Q' compliant (2 and 3 pane doors only)
PAS 24 test data based on 2 pane patio door at 2450mm wide x 2260mm high

0




- B Top rail 'dog bolt'
- 6.8mm laminate / argon / 4mm toughened
- D Interlock handle White, Black, Chrome
- Interlock hook bolts (x3)
- Interlock keeps (x3)
- G Sash hook locks (x8)
- **H** Sliding Sash Internal

PremiLine PRO

Innovative hidden locking system with interlock handle eliminates the needs for unsightly plunge bolts.





Why not consider the other collections available from The Character brand

