

'Choices' PremiLine Sliding Patio Door

Sliding Patio Door

Smooth sliding operation with stylish looks

Standard Specification (includes glazing):

- √ 70mm profile depth with internally glazed sculptured beads
- ✓ Black gaskets with woolpile weatherseals
- ✓ White (chrome and gold effect upgrades) handles
- ✓ Six point six hook locking
- ✓ Fully welded and reinforced
- ✓ Stainless steel adjustable rollers on a stainless steel track
- ✓ Slides on outer track as standard inner track on request
- ✓ 28mm toughened sealed units with Low E Plus Argon gas and warm edge spacer
- ✓ PVCU profiles using 'greenline' 100% lead free stabilizer
- ✓ 20mm low aluminium threshold available (lower weather rating)
- ✓ Mechanically jointed outer frame available
- ✓ Sliding pane external as standard can be specified to be internal
- ✓ 1.4W/m²K 'U' value with Low-E Plus glass

White

Ash

- ✓ 32mm triple glazing option
- ✓ Ultion One Cylinder

Colour Options

Smooth

White



ULTION 1 PLUS

Both sides only white base



Door Sizes - Maximum

2 Pane 3000mm width x 2300mm height 3 Pane 4200mm width x 2300mm height 4 Pane 5800mm width x 2300mm height

NB: The height of the sash must not be more than 2.5 times larger than the width e.g. Frame height 2090mm means minimum frame width of 1600mm



Available both sides or on smooth white



Available on smooth white only



Available on smooth white only extra lead time



6 'Choices' Premiline



PremiLine PRO PAS 24 Upgrade

'Lifetime Homes' and 'Document Q' compliant (2 and 3 pane doors only) PAS 24 test data based on 2 pane patio door at 2450mm wide x 2260mm high



- B Top rail 'dog bolt'
- 6.8mm laminate / argon / 4mm toughened
- D Interlock handle White, Black, Chrome
- Interlock hook bolts (x3)
- Interlock keeps (x3)
- G Sash hook locks (x8)
- **H** Sliding Sash Internal

PremiLine PRO

Innovative hidden locking system with interlock handle eliminates the needs for unsightly plunge bolts.





